

4

3

SH

1/1

REV

C

WINDCHILL VERSION

C.1

1

B

B

DISCHARGE AIR RADIATOR & EXHAUST

Ø 763 [30.0] TYP DOOR SWING

Ø 763 [30.0] TYP DOOR SWING

AIR INTAKE (BOTH SIDES)

5268 [207.4] OVERALL LENGTH

FOR ALL STUB-UP, WEIGHT, AND COG DETAILS, SEE CORRESPONDING OPEN SET DRAWING PER UNIT CONFIGURATION.

A

A

RADIATOR/EXHAUST DISCHARGE AIR

AIR INTAKE

2544 [100.1]

294 [11.6]

3952 [155.6]

1323 [52.1]

3923 [154.4]

DIM X COG

DIM Y COG

1800 [70.9] OVERALL WIDTH

AIR INTAKE

AIR INTAKE

2650 [104.3]

2899 [114.1] OVERALL HEIGHT

DIM Z COG

1679 [66.1]

DRAWING CREATED FROM PRO/ENGINEER 3D FILE. ECO MODIFICATION TO BE APPLIED TO SOLID MODEL ONLY.

DIMENSIONS ARE IN MILLIMETERS [INCHES]

# INSTALLATION DRAWING

GENERAC POWER SYSTEMS OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS SUPPLIED IN CONFIDENCE AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT IS SUPPLIED WITHOUT THE EXPRESS WRITTEN CONSENT OF GENERAC POWER SYSTEMS. ©GENERAC POWER SYSTEMS 2013

ELECTRONICALLY APPROVED  
INSIDE WINDCHILL

## GENERAC

TITLE

L2A ENCLOSURE G21.9L  
60HZ: SG/MG 350,400,450, PG/WG 315,360,405  
50HZ: SG/MG 280,320,360, PG/WG 252,288,324

ISSUE DATE: 04/04/14

SIZE	CAGE NO	DWG NO	REV
B	N/A	OK6048C	C

SCALE	WT-KG	SHEET
0.025		1 of 1

4

3

2

1